

背面视图

PIN ASSIGNMENT:		
PIN	SYMBOL	PIN
1	LEDK	21
2	LEDA	22
3	GN0	23
4	VD0	24
5	R0	25
6	R1	26
7	R2	27
8	R3	28
9	R4	29
10	R5	30
11	R6	31
12	R7	32
13	00	33
14	01	34
15	02	35
16	03	36
17	04	37
18	05	38
19	06	39
20	07	40

EDK	21	B
EDA	22	B

注：肌喷码效果，模拟客户一供实物，喷码不溶于酒精




Figure 1 consists of two parts. The left part is a cross-sectional view of the microfluidic chip, showing five distinct layers: an 'UP BEZEL' at the top, followed by 'TT', 'BL', 'BOTTOM BEZEL', and a 'HOUSING' at the base. The right part is a top-down view of the chip, showing a central square region. This region is divided into three horizontal sections labeled 'R', 'C', and 'B' from top to bottom. Dimension lines indicate the following measurements: a vertical distance of 0.066 from the top edge to the start of section 'R', a vertical distance of 0.198 for the height of section 'R', a vertical distance of 0.198 for the height of section 'C', and a vertical distance of 0.198 for the height of section 'B'.

8. 未标注尺寸公差: ± 0.2 ;

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

LED A+
LED K-
FORWARD CURRENT: $I_F=40\text{mA}$ (CONSTANT CURRENT)
FORWARD VOLTAGE: $V_F=16.2\text{V}$ (MIN.)~ 19.6V (MAX.)
BACKGROUND COLOR: WHITE
BEAD P/W: 01.7TCS2004-P (2PCS)
LUM LUMINANCE: 800cd/m² (7TP)

DIMENSION	1 GRADT	2 GRADT	3 GRADT	4 GRADT
1 ≤ 20	0.05	0.1	0.1	0.2
20 < 1 ≤ 50	0.1	0.15	0.2	0.3
50 < 1 ≤ 100	0.15	0.2	0.25	0.3
100 < 1 ≤ 200	0.2	0.25	0.3	0.5
200 < 1	0.25	0.3	0.5	0.8