

D

C


B

A

Notes:

- 1. Display Type: 3.5" TFT LCD
- 2. Display Mode: Normally Black
- 3. Viewing Direction: All' Clock
- 4. Driver IC: ST7365
- 5. Lcm Brightness: 250cd/m²(MIN), 300cd/m² (TYP)
- 6. Black Light: 6 Chip White LEDs
IF=20mA VF=19.2V(TYP)
- 7. Operating Temp: -10°C TO 60°C
Storage Temp: -20°C TO 70°C
- 8. Unspecified Tolerances :±0.2mm

LED CIRCUIT DIAGRAM:



TOLERANCE TABLE(±)					
DIMENSION	GRADE 1	GRADE 2	GRADE 3	GRADE 4	GRADE 5
L ≤ 20	0.05	0.1	0.15	0.2	0.25
20 < L ≤ 50	0.1	0.15	0.2	0.25	0.3
50 < L ≤ 100	0.15	0.2	0.25	0.3	0.35
100 < L ≤ 200	0.2	0.25	0.3	0.35	0.4
200 < L	0.25	0.3	0.35	0.4	0.45
UNLESS OTHERWISE SPECIFIED					

Customer approve	DYN 帝晶光电 SHEN ZHEN DJN PHOTOELECTRIC TECHNOLOGY CO.,LTD				
	Model No	9G-10035-Z020H	Part No	SZA5007	
	Drawing Title	模组成品	Drawn	丁宝玲	A0
	Drawing No	D-RD-022-23	Checked	秦福军	Unit MM
Scale 1:1		第三视角	Approve	秦福军	Page 1/1

无卤	REACH	RoHS	NO.	CONTENT	DATE
保密等级(秘密)			A		
			M		
			E		
			N		
			D		

